

Reinforced Concrete Beam Project

Herff College of Engineering
2024 Reinforced Concrete Competition



1

Reinforced Concrete Beam Project

➤ The objective of this project is to develop the strongest reinforced concrete (RC) beam as measured by the **cost-adjusted strength-to-weight ratio**.

➤ The strength-to-weight ratio (**SWR**) is:

$$SWR = \frac{\text{Ultimate Load}(lb.)}{\text{Beam Weight}(lb.)}$$

➤ The strength of the beam is the ultimate load recorded during testing.

2

Reinforced Concrete Beam Project

➤ A cost factor will be computed as follows:

If cost < \$1.50 then: **Cost Factor** = 1

If cost > \$1.50 then: **Cost Factor** = $\frac{\$1.50}{\text{Cost}}$


➤ Using your **Cost Factor**, the cost-adjusted **SWR_{Adjusted}** is computed as:

$$SWR_{Adjusted} = SWR \times \text{Cost Factor}$$

3

Reinforced Concrete Beam Project

➤ The concrete beam **must** have a length of 30 in., a height of 6 in., and have a prismatic cross-section. Maximum width of the beam is 6 in.



➤ In designing the reinforced concrete beam groups may consider the use of admixtures, various types of reinforcement, various types of cements and aggregates, and non-rectangular cross-sections.

4

Reinforced Concrete Beam Project

The reinforced concrete beam problem poses several challenges to the student:

1. selection of the shape and size of the cross-section of the beam;
2. design of a concrete mix based on strength and workability;
3. design of the reinforcement (type of reinforcement, amount, and position in the beam), and
4. the prediction of the **SWR** of the beam.

5

Reinforced Concrete Beam Project

The reinforced concrete beam project schedule:

Date	Activity
February 20-22	Introduction; concrete beam #1
February 27-27	Break beam #1; develop concrete beam #2
March 12-14	Break beam #2; develop concrete beam #3
March 19-21	Break beam #3; develop concrete beam #4
March 26-28	Break beam #4; develop final concrete beam
April 2-4	Break final concrete beam

6

Reinforced Concrete Beam Project

The cost of each beam will be estimated using the following data:

Material	Cost
Portland Type I cement	\$130/ton
Coarse aggregate	\$18/ton
Fine aggregate	\$10/ton
Steel reinforcement	\$530/ton
Admixtures - water reducer	\$15/gal.
Admixture - silica fume	\$500/ton
Fiber reinforcement	Market value (see Dr. Camp)

7

Reinforced Concrete Beam Project

The cost of steel may be estimated as follows:

$$\text{Cost of steel} = \frac{A_s L}{1,728 \text{ in.}^3 / \text{ft.}^3} \left(490 \frac{\text{lb.}}{\text{ft.}^3} \right) \left(\frac{\$530}{\text{ton}} \right) \left(\frac{\text{ton}}{2,000 \text{ lb.}} \right)$$

where A_s is the cross-sectional area of steel rebars, L is the length of the steel rebars, and 490 lb./ft.^3 is the unit weight of steel.

8

Reinforced Concrete Beam Project

For example, if one #5 rebar is placed in the beam the steel cost is estimated as:

Bar #	Diameter (in)	As (in ²)
2	0.125	0.0245
3	0.375	0.11
4	0.500	0.20
5	0.625	0.31
6	0.750	0.44
7	0.875	0.60
8	1.000	0.79
9	1.128	1.00
10	1.270	1.27
11	1.410	1.56

Cost of steel

$$= \frac{(0.31 \text{ in.}^2)(30 \text{ in.})}{1,728 \text{ in.}^3 / \text{ft.}^3} \left(490 \frac{\text{lb.}}{\text{ft.}^3} \right) \left(\frac{\$530}{\text{ton}} \right) \left(\frac{\text{ton}}{2,000 \text{ lb.}} \right) = \$0.70$$

9

Reinforced Concrete Beam Project

Consider the following mix for a cubic yard of concrete developed using the ACI mix design procedure.

Component	Amount (lb.)
Water	304
Cement	708
Coarse aggregate	1,824
Fine aggregate	1,131

10

Reinforced Concrete Beam Project

The cost of the concrete required for a 4 in. by 6 in. by 30 in. beam is estimated as:

$$\text{Cost of cement} = \frac{4 \text{ in.}(6 \text{ in.})30 \text{ in.}}{1,728 \text{ in.}^3 / \text{ft.}^3} \left(\frac{708 \text{ lb.}}{27 \text{ ft.}^3} \right) \left(\frac{\$130}{\text{ton}} \right) \left(\frac{\text{ton}}{2,000 \text{ lb.}} \right) = \$0.71$$

$$\text{Cost of coarse aggregate} = \frac{4 \text{ in.}(6 \text{ in.})30 \text{ in.}}{1,728 \text{ in.}^3 / \text{ft.}^3} \left(\frac{1,824 \text{ lb.}}{27 \text{ ft.}^3} \right) \left(\frac{\$18}{\text{ton}} \right) \left(\frac{\text{ton}}{2,000 \text{ lb.}} \right) = \$0.25$$

11

Reinforced Concrete Beam Project

The cost of the concrete required for a 4 in. by 6 in. by 30 in. beam is estimated as:

$$\text{Cost of fine aggregate} = \frac{4 \text{ in.}(6 \text{ in.})30 \text{ in.}}{1,728 \text{ in.}^3 / \text{ft.}^3} \left(\frac{1,131 \text{ lb.}}{27 \text{ ft.}^3} \right) \left(\frac{\$10}{\text{ton}} \right) \left(\frac{\text{ton}}{2,000 \text{ lb.}} \right) = \$0.09$$

The cost concrete is estimated as: \$1.05

The cost reinforced concrete beam is estimated as: \$1.75

12

Reinforced Concrete Beam Project

The cost adjustment for the reinforced concrete beam is :

If cost < \$1.50 then: $Cost\ Factor = 1$

If cost > \$1.50 then: $Cost\ Factor = \frac{\$1.50}{Cost}$

13

Reinforced Concrete Beam Project

For example, if the unadjusted **SWR** for a beam is 210 and the cost is \$1.75, then the cost adjusted **SWR** is:

If cost > \$1.50 then: $Cost\ Factor = \frac{\$1.50}{Cost}$

$$SWR_{Adjusted} = 210 \times \frac{\$1.50}{\$1.75} = 180$$

14

Reinforced Concrete Beam Project

If the cost were \$1.35, then the cost adjusted **SWR** is:

If cost < \$1.50 then: $Cost\ Factor = 1$

$$SWR_{Adjusted} = SWR \times Cost\ Factor$$

$$SWR_{Adjusted} = 210 \times 1 = 210$$

15

Reinforced Concrete Beam Project



16

Reinforced Concrete Beam Project

Any questions?



17