Example 6b-1: The beam supports a uniform dead load of 500 N/m and a single live concentrated force of 3 kN. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at C.



Example 6b-1: The beam supports a uniform dead load of 500 N/m and a single live concentrated force of 3 kN. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at C.



Example 6b-1: The beam supports a uniform dead load of 500 N/m and a single live concentrated force of 3 kN. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at C.



Example 6b-2: Determine the maximum positive shear force that can be developed at point D in the beam shown below due to a concentrated live load of 4 k, a uniform live load of 300 lb/ft, and a dead load of 200 lb/ft.



Example 6b-2: Determine the maximum positive shear force that can be developed at point D in the beam shown below due to a concentrated live load of 4 k, a uniform live load of 300 lb/ft, and a dead load of 200 lb/ft.



Example 6b-3: The beam supports a uniform dead load of 300 lb/ft, a uniform live load of 600 lb/ft, and a single live concentrated force of 20 k. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at C.



Example 6b-3: The beam supports a uniform dead load of 300 lb/ft, a uniform live load of 600 lb/ft, and a single live concentrated force of 20 k. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at C.



Example 6b-4: The beam supports a uniform dead load of 200 lb/ft, a uniform live load of 400 lb/ft, and a single live concentrated force of 10 k. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at B.



Example 6b-4: The beam supports a uniform dead load of 200 lb/ft, a uniform live load of 400 lb/ft, and a single live concentrated force of 10 k. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at B.



Example 6b-5: The beam supports a uniform dead load of 200 lb/ft, a uniform live load of 600 lb/ft, and a single live concentrated force of 20 k. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at E.



Example 6b-5: The beam supports a uniform dead load of 200 lb/ft, a uniform live load of 400 lb/ft, and a single live concentrated force of 10 k. Determine (a) the maximum positive moment at C and (b) the maximum positive shear at E.



Example 6b-6: The beam supports a uniform dead load of 200 lb/ft, a uniform live load of 600 lb/ft, and a single live concentrated force of 20 k. Determine (a) the maximum positive moment at B and (b) the maximum positive shear at C.



Example 6b-6: The beam supports a uniform dead load of 200 lb/ft, a uniform live load of 600 lb/ft, and a single live concentrated force of 20 k. Determine (a) the maximum positive moment at B and (b) the maximum positive shear at C.



6–18. The beam is used to support a dead load of 500 lb/ft, a uniform live load of 2 k/ft, and a concentrated live load of 8 k. Determine (a) the maximum positive (upward) reaction at A, (b) the maximum positive moment at E, and (c) the maximum positive shear just to the right of the support at C. Assume A and C are rollers and D is a pin.



6–18. The beam is used to support a dead load of 500 lb/ft, a uniform live load of 2 k/ft, and a concentrated live load of 8 k. Determine (a) the maximum positive (upward) reaction at A, (b) the maximum positive moment at E, and (c) the maximum positive shear just to the right of the support at C. Assume A and C are rollers and D is a pin.



6–18. The beam is used to support a dead load of 500 lb/ft, a uniform live load of 2 k/ft, and a concentrated live load of 8 k. Determine (a) the maximum positive (upward) reaction at A, (b) the maximum positive moment at E, and (c) the maximum positive shear just to the right of the support at C. Assume A and C are rollers and D is a pin.

