



## Oceanic-Continental Collision (subduction)




Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 7

## Types of Earthquakes

About 90% of the earth's seismicity occurs at plate boundaries on faults directly forming the interface between two plates. These are called **plate-boundary or interplate** earthquakes.

The other 10% occur away from the plate boundary, in the interior of plates. These are called **intraplate** earthquakes.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 8

## Plate-boundary Earthquakes

**A plate-boundary (interplate) earthquake** is an earthquake that occurs along a fault associated with an active plate boundary. An example of this type of boundary is the San Andreas Fault in California.

⇒ Frequent occurrence, relatively well understood behavior, as per plate tectonic theory.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 9

## San Andreas Fault – Well Known Plate Boundary




Photo courtesy of: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 10

## Intraplate Earthquakes


**An intraplate earthquake** is an earthquake that occurs along a fault within the stable region of a plate's interior (SICR). Examples are the 1811-12 Madrid, MO earthquakes, the 1886 Charleston, South Carolina, earthquake, and, more recently, the Bhuj, India, earthquake in 2001.

⇒ Infrequent occurrence, poorly understood, difficult to study.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 11

## Historical Large Intraplate Earthquakes



\* Largest historical earthquakes in contiguous United States occurred east of the Mississippi!!



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 12


## Why Intraplate Earthquakes?

- Ancient “Rifts” – very old fractures in crust related to previous episodes of continental spreading.
- “Weak Spots” – heating up and thinning of lower crust such that the brittle-ductile transition (molten rock/crust boundary) migrates to a higher level. Because the overlying crust becomes thinner, stresses become more concentrated in the crust.




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 13

## Why Intraplate Earthquakes?



Figures from USGS

Example of 700 million year old rift zone:



Rift allows stress concentrations



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 14

## Why Intraplate Earthquakes?

- Thermal destabilization -- sinking of mafic rock mass (rock mass of heavy minerals) into underlying molten rock. As mafic block sinks, stresses are concentrated in overlying crust. Process thought to be due to rock density anomalies combined with thermal processes.
- Other localized mechanisms? (meteor impact craters, etc.)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 15

## Seismicity of North America




Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 16

## California Seismicity

Seismicity relatively well understood



Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 17

## Pacific Northwest – Cascadia Subduction Zone

Ultimate magnitude potential?



Figure Credit: USGS



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 18

## Idaho, Utah, Wyoming

Recurring events along Wasatch Fault




Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 19

## Central US Seismic Zones


- Who really knows for sure?
- The Reelfoot Rift is associated with many events in this region.



Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 20



Isoseismal Map from New Madrid Earthquake, Dec. 16, 1811

Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 21

## Reelfoot Rift Associated with Central US Earthquakes




Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 22

## 1811-12 New Madrid Earthquakes (three M8+)

Isoseismal Map -- Dec. 16, 1811



Reelfoot Lake, Tennessee, was created due to subsidence and tectonic change



Figure and photo credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 23

## How Big is the CEUS Problem?

### New Madrid Seismic Zone

- Highest hazard in the US outside the WUS
- M1-2 every other day (200 per year)
- M3 every year (felt)
- M4 every 1.5 years (local minor damage)
- M5 every 10 years (damaging event)
- M6 every 80 years (last one in 1895)
- M8+ every 400-600 years? (last one in 1812)
- M6-7.5 has 25-40% chance in 50 years
- M8+ has 4-10% chance in 50 years



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 24

### How Big Is the CEUS Problem?


- A recurrence of the New Madrid earthquake, postulated with a 4-10% probability in the next 50 years, has been estimated to cause a total loss potential of \$200 billion with 26 states affected.
- Approximately 2/3 of the projected losses will be due to **interruptions in business operations and the transport of goods across mid-America.**
- This **economic loss is of the same order as that caused by the terrorist attacks of September 11, 2001 (NRC, 2003).**



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 25

### Southeastern Seismicity

- Tennessee relatively active
- 1886 South Carolina event not fully explained
- Magnetic signature from North Carolina to Georgia similar to Charleston area; same potential?



Epicenters of earthquakes (M > 0.0) in the southeastern US from 1977 through 1999.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 26

### Isoseismal Map from the 1886 Charleston Earthquake



Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 27

### Isoseismal Map for the Giles County, Virginia, Earthquake of May 31, 1897; M ≈ 6?



Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 28

### Recent Paleoseismological Studies

- Studies in the central and southeastern United States indicate recurring large prehistoric earthquakes – this has increased hazard
- Studies in Pacific Northwest debatable



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 29

### Isoseismal Map from the 1886 Charleston Earthquake



Figure credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 30



### 1886 Charleston Earthquake



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 31

### 1886 Liquefaction Feature




Photo credit: USGS



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 32

### Prehistoric Sand Crater in Trench Wall



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 33

### Schematic of Ancient Sand Crater




Figure from Obermeier, 1998.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 34

### Ages of Earthquake-induced Liquefaction Features Found in Charleston Region\*


- 600 ybp
- 1250 ybp
- 3250 ybp
- 5150 ybp
- > 5150 ybp

\* Study led to increased seismic design values in South Carolina.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 35

### Virginia Tech Paleoliquefaction Studies




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 36

### Artesian Condition?



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 37


### Types of Faults



(a) Strike-slip fault



(c) Reverse fault




(b) Normal fault



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 38


### Elastic Rebound Theory

Time = 0 Years




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 39

Time = 40 Years  
(strain building)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 40

Time = 41 Years  
(strain energy released)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 41

### San Andreas Fault, San Francisco, 1906




Photo credit: USGS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 42

## Moment Magnitude

- Seismic Moment =  $M_0 = \mu A D$  [Units = Force x Distance]

where:


$\mu$  = modulus of rigidity ( $\sim 3.5 \times 10^{11}$  dynes/cm<sup>2</sup> typical)  
 $A$  = fault rupture area ( $W \times L$ ); where typical  $L$  for big earthquake  $\approx 100$  km, and  $W \approx 10$  to 20 km  
 $D$  = fault displacement (typical  $\approx 2$  m for big quake)

- Moment magnitude:  $M_W = 2/3(\log_{10} M_0 / 1.5) + 10.7$



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 43

## Earthquake Source and Seismic Waves




- Body waves are generated at the source and they radiate in all directions.
- As they go through layers, they are *reflected*, *refracted* and *transformed*.




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 44

## Seismic Wave Forms (Body Waves)




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 45

## Seismic Wave Forms (Surface Waves)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 46

## Earthquake Source and Seismic Waves




P – Primary waves  
 SH – Horizontally polarized S waves  
 SV – Vertically polarized S waves

Waves bend upwards as they approach the ground surface because of less competent material near the surface – Snell's Law



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 47


## Seismic Waves



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 48



## Reflection and Refraction at Boundary




- Amplitude and direction of reflected and refracted waves with respect to the incoming wave is given by Snell's Law
- Earth's crust is layered, with seismic velocities increasing with depth; therefore as waves approach ground surface wave path will get near-vertical



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 49

## Ground Motion Estimation



What ground motions at Site A and B? Two steps:

1. Define earthquake scenario
2. Estimate site response and ground motions

⇒ Must be done in context of structure, type of analysis



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 50

## Different Structures, Responses, Analyses, and Issues



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 51

## Ground Motion Estimation

- No "universal" set of ground motions for any region.
- Uncertainties are inherent to the process and will cause differences in results.
- Judgment is required, even with probability.
- Inconsistency among governing agencies.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 52


## Ground Motion Estimation

- Two analyses using same models and basic parameters can give different answers (EPRI vs. NRC/LLNL studies in 1980s).
- Where time and effort are focused during the process is function of structure/system being analyzed.
- Not possible to predict actual motion that will occur at a site; mainly concerned with capturing characteristics important to performance of project.
- Seismologist and engineers must have continuous feedback!



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 53


## Structure/System Considerations



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 54

## Structure/System Issues

- Place emphasis on issues important to the specific project.



**Example:** If this is not an important part of the spectrum, do not spend extra time and effort on issues that affect this.

- Also, think in terms of system performance.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 55

## Consider Performance of Entire System



Internal systems



Site effects, liquefaction, etc.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 56

## Structure/System Considerations

- Type of structure (building, embankment dam, etc.)
- Type and purpose of analysis – (linear elastic? time history? liquefaction?)
- Parameters that are important (pga? duration?)
- Typical process: seismologist  $\Rightarrow$  geotech engineer  $\Rightarrow$  structural engineer
- Seismologists and end user must be closely involved with continuous feedback
- Selection of earthquake scenario is most important task – (do not want precise analysis of inaccurate model)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 57

## Seismic Hazard and Seismic Risk

**Seismic hazard evaluation**  $\Rightarrow$  involves establishing earthquake ground motion parameters for use in evaluating a site/facility during seismic loading. By assessing the vulnerability of the site and the facility under various levels of these ground motion parameters, the **seismic risk** for the site/facility can then be evaluated.

- Seismic hazard** – the expected occurrence of future seismic events
- Seismic risk** – the expected consequences of future seismic events



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 58

## Approaches to Seismic Hazard Analysis

### Deterministic:

“The earthquake hazard for the site is a peak ground acceleration of 0.35 g resulting from an earthquake of magnitude 7 on the Woodstock Fault at a distance of 18 miles from the site.”

### Probabilistic:

“The earthquake hazard for the site is a peak ground acceleration of 0.25 g, with a 2 percent probability of being exceeded in 50 years.”



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 59

## Deterministic Hazard Analysis

- Identify and characterize source zones that may produce significant ground shaking at the site
- Determine the distance from each source zone to the site
- Select the controlling earthquake scenario(s)
- Calculate the ground motions at the site using a regional attenuation relationship



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 60

### Steps in Deterministic Seismic Hazard Analysis

**1) Sources\***

**2) Controlling earthquake**

Fixed Distance R\*

Fixed Magnitude M\*

**3) Ground motion attenuation**

**4) Hazard at site**

"The earthquake hazard for the site is a pga of 0.35 g resulting from an earthquake of M7 on the Woodstock Fault at a distance of 18 miles from the site."

\*Can use probability to help define these.

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 61

### Example Deterministic Analysis (Kramer, 1996)

Source	M	D (km)	PGA (g)
1	7.3	23.7	0.42
2	7.7	25.0	0.57
3	5.0	60.0	0.02

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 62

### Advantages of Deterministic Approach

- Analysis is relatively “transparent”; effects of individual elements can be understood and judged more readily.
- Requires less expertise than probabilistic analysis.
- Anchored in reality.

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 63

### Disadvantages of Deterministic Approach

- Does not consider inherent uncertainties in seismic hazard estimation (i.e., maximum magnitude, ground motion attenuation).
- Relative likelihood of events not considered (EUS vs. WUS); therefore, inconsistent levels of risk.
- Does not allow rational determination of scenario design events in many cases.
- More dependent upon analyst.

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 64

### Probabilistic Seismic Hazard Analysis

⇒ Considers where, how big, and how often.

- Identify and characterize source zones that may produce significant ground shaking at the site including the spatial distribution and probability of eq's in each zone.
- Characterize the temporal distribution and probability of earthquakes in each source zone via a recurrence relationship and probability model.
- Select a regional attenuation relationship and associated uncertainty to calculate the variation of ground motion parameters with magnitude & distance.
- Calculate the hazard by integrating over magnitude and distance for each source zone.

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 65

### Steps in Probabilistic Seismic Hazard Analysis



**1) Sources**

**2) Recurrence**

**3) Ground motion**

**4) Probability of exceedance**

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 66



- ### We Commonly Use Two Approaches to Predict the Likelihood of Earthquakes
- Time-independent (Poisson Model)
  - Time-dependent Models
- FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 69

- ### Poisson Model
- The simplest, most used model for earthquake probability.
  - It is a time-independent model -- the probability that an earthquake will occur in an interval of time starting from now does not depend on when "now" is, because a Poisson process has no "memory."
- FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 70

### Poisson Distribution (general form)

$$P(X = k) = \frac{(\lambda t)^k e^{-(\lambda t)}}{k!}$$

where  $\lambda$  = rate (events/year)  
 $t$  = exposure interval  
 $k$  = no. of events

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 71

### Poisson Distribution (for one event)

$$P = 1 - e^{-\lambda t}$$

where  $\lambda$  = rate (events/year) ← key!!  
 $t$  = exposure interval  
 $1/\lambda$  = return period

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 72

### Poisson Model

- Note that the probabilistic earthquake risk level can be put in the form of an earthquake return interval:

$$\text{Earthquake Return Period} = t / \ln(1 - PE)$$

PE	t	Return Period
10%	50 yrs.	475
5%	50 yrs.	975
2%	50 yrs.	2475

Note that when the exponent of the equation,  $\lambda t$ , is small, then  $P \approx \lambda t$ .



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 73

### Example- Poisson Model

Is a 2%/50-year event the same as a 10%/250-year event?

– For 2%/50 years, we have  $50 / (-\ln(1 - 0.02)) = 2,475$  year return period

– For 10%/250 years, we have  $250 / (-\ln(1 - 0.10)) = 2,372$  year return period

⇒ These events (probabilities) are not exactly equal, but are “equal” from design standpoint.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 74


### Time-Dependent Models

- Used less than simpler Poisson model
- Time-dependent means that the probability of a large earthquake is small immediately after the last, and then grows with time.
- Such models use various probability density functions to describe the time between earthquakes including Gaussian, log-normal, and Weibull distributions.





Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 75

### Example Probabilistic Analysis (Kramer)




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 76

### Result of Probabilistic Hazard Analysis






Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 77

### Use of PGA Seismic Hazard Curve



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 78





- ### Uniform Hazard Spectrum
- Developed from *probabilistic* analysis.
  - Represents contributions from small local and large distant earthquakes.
  - May be overly conservative for modal response spectrum analysis.
  - May not be appropriate for artificial ground motion generation, especially in CEUS.
- FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 82

- ### Advantages of Probabilistic Approach
- Reflects true state of knowledge and lack thereof.
  - Consider inherent uncertainties in seismic hazard estimation (i.e., maximum magnitude, ground motion attenuation).
  - Considers likelihood of events considered; basis for consistent levels of risk established.
  - Allows more rationale comparison among many scenarios and to other hazards.
  - Less dependent upon analyst.
- FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 83

- ### Disadvantages of Probabilistic Approach
- Analyses are not transparent; the effects of individual parameters cannot be easily recognized and understood.
  - “Quantitatively seductive” -- encourages use of precision that is out of proportion with the accuracy with which the input is known.
  - Requires special expertise.
  - May provide unrealistic scenarios (i.e., probabilistic design event could correspond to location where actual fault does not exist).
  - Analyst still has big influence (methods, etc.).
- FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 84

## Probabilistic vs. Deterministic


- Results of probabilistic and deterministic analyses are often similar in the WUS; not true for CEUS.
- Deterministic scenarios typically very difficult to define in CEUS.
- Best to use integrated or hybrid method that combines both approaches.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 85

## Deaggregation of the PSHA

- Each bar represents an event that exceeds a specified ground motion at 1 Hz – Washington, DC, example.; note mean and modal values.




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 86

## Hazard Scenario – Example



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 87

## 1,950 Year Uniform Hazard Spectrum for Site



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 88


## Deaggregation Plots for 1,950 Year Event (5%/100 yr)

Scenarios A & B  
M6@25 km & M7.5 @101 km

Scenarios A & B  
M6@25 km & M7.5 @101 km


Scenarios A, B, & C?  
M6@25 km, M7.5 @101 km,  
and M7.5@ 200 km

⇒ Scenarios A & B  
selected based on T of  
structure (< 1.0 sec.)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 89

## Stochastic Simulations of Ground Acceleration for M = 6.0 at 25 km (Scenario A)




From the top, vertical, North-South and East-West components



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 90

### Stochastic Simulations of Ground Acceleration for M = 7.5 at 101 km (Scenario B)



Vertical, fault normal and fault parallel refer to finite fault calculations, and show 3-orthogonal components of motion, oriented with respect to source



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 91

### Discussion of Selected Scenarios A & B

- What kind of analysis to be performed?
- Is duration important, or just pga?
- Basic question: “Does it matter which event caused motions to be exceeded?”
- Seismologist and end user should be closely linked from the beginning!!



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 92

### National Seismic Hazard Maps

- Developed by U.S. Geological Survey.
- Adopted (almost exactly) by building codes and reference standards (i.e., IBC2003) and, therefore, very important!!!
- Based on probability ⇒ maps show contours of maximum expected ground motion for a given level of certainty (90%, 98%, etc.) in 50 years; or, said differently, contours of ground motions that have a common given probability of exceedance, PE, in 50 years (10%, 2%, etc.).



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 93


### Earthquake Probability Levels

- Note that the term “2500 year earthquake” does not indicate an event that occurs once every 2,500 years!
- Rather, this term reflects a **probability**, that is, the earthquake event that has a probability of 1 in 2500 of occurring in one year.
- For instance, the “100-year flood” can actually occur several years in a row or even several times in one year (as occurred in the 1990s in Virginia).




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 94

### USGS PROBABILISTIC HAZARD MAPS (2002/2003 versions most recent)\*



HAZARD MAP



Uniform Hazard Spectra

\*2002 versions revised April 2003



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 95




### USGS PROBABILISTIC HAZARD MAPS (and NEHRP Provisions Maps)

#### Earthquake Spectra

Theme Issue : Seismic Design Provisions and Guidelines  
Volume 16, Number 1  
February, 2000



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 96



### USGS Website: ZIP CODE Values

<http://eqint.cr.usgs.gov/eq/html/zipcode.html>

```

The input zip-code is 80203. (DENVER)
ZIP CODE                80203
LOCATION                  39.7310 Lat. -104.9815 Long.
DISTANCE TO NEAREST GRID POINT 3.7898 kms
NEAREST GRID POINT      39.7 Lat. -105.0 Long.
Probabilistic ground motion values, in %g, at the Nearest Grid
point are:

          10%PE in 50 yr   5%PE in 50 yr   2%PE in 50 yr
PGA       3.299764         5.207589         9.642159
0.2 sec SA 7.728900         11.917400        19.921591
0.3 sec SA 6.178438         9.507714         16.133711
1.0 sec SA 2.334019         3.601994         5.879917
    
```

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 100

### USGS Seismic Hazard Maps

- Hazard in some areas increased relative to previous maps due to recent studies.
- Maps developed for motions on B-C soil boundary (soft rock).
- Maps do not account for regional geological effects such as deep profiles of unconsolidated sediments– this is big effect in CEUS (i.e., in Charleston ~1 km thick).
- New 2002 versions of maps revised in April 2003.


FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 101

### National Seismic Hazard Maps Uses:


- can illustrate relative probability of a given level of earthquake ground motion of one part of the country relative to another.
- illustrate the relative demand on structures in one region relative to another, at a given probability level.
- as per building codes, use maps as benchmark to determine the resistance required by buildings to resist damaging levels of ground motion.
- with judgment and sometimes special procedures, use maps to determine the input ground motions for geotechnical earthquake analyses (liquefaction, etc.)

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 102


### USGS Seismic Hazard Curves for Various Cities




### How Does CEUS and WUS Seismic Risk Compare?




### 1886 Charleston Earthquake Felt Over EUS!



### WUS vs. CEUS Attenuation



### US Population Density



### California Seismicity Well Understood

Seismicity relatively well understood





### Seismically Weak Infrastructure in CEUS



FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 109

### WUS and CEUS Risk Comparison

- CEUS has potential for recurring large earthquakes
- Attenuation lower in CEUS
- Weak structures not “weeded out” in CEUS
- “Adolescent” seismic practice in CEUS
- “Human inertia” in CEUS
- Much more uncertainty in CEUS
- Bottom line ⇒ *seismic risk in CEUS and WUS is comparable!*

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 110

### Example of Inadequately Reinforced, Nonductile Structure, 1989 Loma Prieta EQ



Cypress Overpass

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 111




FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 112



FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 113



FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 114



## WUS and CEUS Risk Comparison Summary

- CEUS has potential for recurring large EQs
- Attenuation lower in CEUS
- Abundance of weak, non-ductile structures in CEUS; weakest not “weeded out”
- Immature seismic practice in CEUS
- “Human inertia” in CEUS; little awareness
- Much more uncertainty in CEUS
- Areas with poor soils in CEUS
- Bottom line  $\Rightarrow$  *seismic risk in CEUS and WUS is comparable!*



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 121


## Issues To Think About

- Good analogy  $\Rightarrow$  Kobe is to Tokyo, as CEUS is to the WUS
- Kobe M6.9 (> \$120 billion losses); weaker infrastructure, poor soil conditions
- Remember  $\Rightarrow$  most expensive US natural disaster (Northridge, EQ ~\$30 billion) was moderate earthquake on minor fault on fringe of Los Angeles



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 122

## Estimation of Ground Motions



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 123

## Estimation of Ground Motions

We typically need one or more of these:

- Peak ground motion parameters (peak ground accelerations, peak velocities); or, duration.
- Spectral parameters (response spectra, Fourier spectra, uniform hazard spectra)
- Time history of acceleration, velocity, etc.  $\Rightarrow$  needed for advanced and/or specialized analyses.
- We typically need these parameters for ground surface



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 124

## Ground Motions at a Site Are Related To:

- Source conditions— amount of energy released, nature of fault rupture, etc.
- Path effects – anelastic attenuation, geometrical spreading, etc.
- Site effects – site response, soil amplification, etc.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 125

## Source Conditions Include:

- Stress drop
- Source depth
- Size of the rupture area
- Slip distribution (amount and distribution of static displacement on the fault plane)
- Rise time (time for the fault slip to complete at a given point on the fault plane)
- Type of faulting
- Rupture directivity



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 126

## Transmission Path Includes:

- Crustal structure
- Shear-wave velocity (or Q) and damping characteristics of the crustal rock



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 127


## Site Conditions Include:

- Rock properties beneath the site to depths of up to about 2 km (hard crystalline rock)
- Local soil conditions at the site to depths of up to several hundred feet (typically)
- Topography of the site



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 128

## Effects of Magnitude




From USACE, 2000

Figure 3-1. An example of accelerograms recorded in 1985 and 1986 on the Guerrero accelerograph array (Anderson and Gaus 1988), courtesy of Earthquake Engineering Research Institute, Oakland, CA)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 129

## Effects of Magnitude




From USACE, 2000

Figure 3-2. Effect of magnitude  $M$  on response spectral shape of rock motions based on observation (Anderson et al. 1993), 35 km distance from source to site, 5 percent damping.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 130

## Effects of Distance




From USACE, 2000

Figure 3-4. Variation of spectral shape with distance for rock recordings of the October 17, 1989, Loma Prieta earthquake.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 131

## Effects of Distance



From USACE, 2000


Figure 3-6. Effect of distance on response spectral shapes for a moment magnitude  $M_w$  6.5 earthquake using western North American parameters (Silva and Green 1998), courtesy of Earthquake Engineering Research Institute, Oakland, CA)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 132



## Regional Effects



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 133

## Effect of Local Site Conditions




Figure adapted from Seed and Idriss (1984); EERI.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 134

## Special Near-source Effects

“Near-source” can be interpreted differently. For many engineering applications, a zone within about 20 km of the fault rupture is considered near-source. Other cases near-source is considered within a distance roughly equal to the ruptured length of the fault; 20 to 60 km typical

Near-source effects:

- Directivity
- Fling
- Radiation pattern



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 135

## Important Near-Fault Effects

Two Causes of large velocity pulses:

- Directivity
- Fling



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 136

## Causes of Velocity Pulses

Directivity:

- Related to the direction of the rupture front
  - Forward directivity: rupture toward the site (site away from the epicenter)
  - Backward directivity: rupture away from the site (site near the epicenter)

Fling:

- Related to the permanent tectonic deformation at the site



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 137




## Velocity Pulses

- Directivity
  - Two-sided velocity pulse due to constructive interference of SH waves from generated from parts of the rupture located between the site and epicenter; affects fault-normal component
  - Occurs at sites located close to the fault but away from the epicenter
- Fling
  - One-sided velocity pulse due to tectonic deformation; affects fault-parallel component
  - Occurs at sites located near the fault rupture independent of the epicenter location






Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 138






- ### Effects of Fling
- Not currently known which types of structures are sensitive to fling ground motions.
  - Preliminary results indicate some long-span structure may be sensitive to fling.
  - Need to evaluate various types of structures to ground motions with and without fling to determine the effect.
- Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 142





- ### Effects of Fling and Directivity
- Directivity can cause amplification of motions for sites close to the fault rupture.
  - Unclear as to engineering significance of fling.
  - Current attenuation relations do not include these effects.



- ### Other Important Effects
- Also, vertical motions tend to be higher than 2/3 maximum horizontal motions when near-source.
  - Subduction zone EQs vs. shallow EQs
  - Topographical effects (especially basins).
  - Surface waves may be important for certain long-span structures (relative motion among supports).
  - Others...

- ### Three Classes of Methods for Ground Motion Estimates
- Generalized, simplified (i.e., IBC2003) ←
  - Site-specific, simplified (i.e., attenuation curves, site amplification factors)
  - Site-specific, rigorous (time history analysis)
- Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 149

- ### Generalized, Simplified (i.e., IBC 2003)
- Simple to use.
  - Based on probabilistic maps.
  - Does not account for regional geological effects (maps assume standard depth for B-C boundary and profile layering) ⇒ in WUS, B-C boundary is shallow bedrock, but in some CEUS areas the B-C boundary is deep as 1 km.
  - Accounts for local site effects in general manner– cannot handle special site conditions.
  - Not well-suited to many geotechnical analyses (no magnitude, UHS approach, etc.).
- Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 150

## IBC 2003 - Overview

- Developed from a combination of three legacy model codes (UBC, BOCA, & SBC).
- Based largely on FEMA 368 and 369, *NEHRP Recommended Provisions and Commentary*.
- Adopted in 45 states (as of July 2004) and by the DoD.
- Incorporates most recent (2002/2003) USGS seismic hazard maps; USGS map values capped in some areas by IBC 2003.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 151

## IBC 2003 – General Procedure

- Maximum Considered Earthquake (MCE) based on 2002/2003 USGS probabilistic hazard maps (deterministic limits used in high seismicity areas – here hazard can be driven by tails of distributions).
- Maps provide and spectral accelerations for  $T = 0.2$  sec ( $S_s$ ), and  $T = 1.0$  sec ( $S_1$ ) for B-C boundary.
- Local soil conditions considered using site coefficients ( $F_a$  and  $F_v$ )
- Develop design spectrum using S and F values




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 152


## IBC 2003 – General Procedure

- Determine  $S_s$  and  $S_1$  from the maps

$S_s$  (0.2 sec) map



$S_1$  (1.0 sec) map



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 153

## IBC 2003 – General Procedure

- Determine site class based on top 30 m:

TABLE 1615.1.1  
SITE CLASS DEFINITIONS

SITE CLASS	SOL PROFILE NAME	AVERAGE PROPERTIES IN TOP 100 feet, AS PER SECTION 1615.1.5		
		Soil shear wave velocity $V_s$ (ft/s)	Standard penetration resistance, $N$	Soil undrained shear strength, $S_u$ (psf)
A	Hard rock	$V_s > 5,000$	Not applicable	Not applicable
B	Rock	$2,500 < V_s \leq 5,000$	Not applicable	Not applicable
C	Very dense soil and soft rock	$1,200 < V_s \leq 2,500$	$N > 50$	$S_u > 2,000$
D	Stiff soil profile	$600 < V_s \leq 1,200$	$15 \leq N \leq 50$	$1,000 \leq S_u \leq 2,000$
E	Soft soil profile	$V_s < 600$	$N < 15$	$S_u < 1,000$

Any profile with more than 10 feet of soil having the following characteristics:  
 1. Plasticity index  $PI > 20$ ;  
 2. Moisture content  $w > 40\%$ , and  
 3. Undrained shear strength  $S_u < 500$  psf

Any profile containing soils having one or more of the following characteristics:  
 1. Soils vulnerable to potential failure or collapse under seismic loading such as liquefiable soils, quick and highly sensitive clays, collapsible weakly cemented soils.  
 2. Peats and/or highly organic clays ( $H > 10$  feet of peat and/or highly organic clay where  $H$  = thickness of soil)  
 3. Very high plasticity clays ( $PI > 25$  feet with plasticity index  $PI > 75$ )  
 4. Very thick soft/medium stiff clays ( $H > 120$  ft)

For SI: 1 foot = 304.8 mm, 1 square foot = 0.9029 m<sup>2</sup>, 1 pound per square foot = 0.0479 kPa.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 154

## IBC 2003 – General Procedure

- Determine  $F_a$  &  $F_v$  values from  $S_s$ ,  $S_1$  and site class:

TABLE 1615.1.2(1)  
VALUES OF SITE COEFFICIENT  $F_a$  AS A FUNCTION OF SITE CLASS AND MAPPED SPECTRAL RESPONSE ACCELERATION AT SHORT PERIODS ( $S_s$ )<sup>a</sup>

SITE CLASS	MAPPED SPECTRAL RESPONSE ACCELERATION AT SHORT PERIODS				
	$S_s \leq 0.25$	$S_s = 0.50$	$S_s = 0.75$	$S_s = 1.00$	$S_s = 1.25$
A	0.8	0.8	0.8	0.8	0.8
B	1.0	1.0	1.0	1.0	1.0
C	1.2	1.2	1.1	1.0	1.0
D	1.6	1.4	1.2	1.1	1.0
E	2.5	1.7	1.2	0.9	Note b
F	Note b	Note b	Note b	Note b	Note b

a. Use straight line interpolation for intermediate values of mapped spectral acceleration at short period,  $S_s$ .  
 b. Site-specific geotechnical investigation and dynamic site response analysis shall be performed to determine appropriate values.

TABLE 1615.1.2(2)  
VALUES OF SITE COEFFICIENT  $F_v$  AS A FUNCTION OF SITE CLASS AND MAPPED SPECTRAL RESPONSE ACCELERATION AT 1 SECOND PERIOD ( $S_1$ )<sup>a</sup>



SITE CLASS	MAPPED SPECTRAL RESPONSE ACCELERATION AT 1 SECOND PERIOD				
	$S_1 \leq 0.1$	$S_1 = 0.2$	$S_1 = 0.3$	$S_1 = 0.4$	$S_1 \geq 0.5$
A	0.8	0.8	0.8	0.8	0.8
B	1.0	1.0	1.0	1.0	1.0
C	1.7	1.6	1.5	1.4	1.3
D	2.4	2.0	1.8	1.6	1.5
E	3.5	3.2	2.8	2.4	Note b
F	Note b	Note b	Note b	Note b	Note b

a. Use straight line interpolation for intermediate values of mapped spectral acceleration at 1-second period,  $S_1$ .  
 b. Site-specific geotechnical investigation and dynamic site response analysis shall be performed to determine appropriate values.




Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 155

## NEHRP Provisions Site Amplification for Site Classes A through E



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 156

### Example: 2% in 50 Year Spectrum Modified for Site Class D (5% Damping)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 157

### IBC 2003 - General Procedure

- Adjust MCE values of  $S_s$  and  $S_1$  for local site effects:

$$S_{MS} = F_a \cdot S_s \quad S_{M1} = F_v \cdot S_1$$

- Calculate the spectral design values  $S_{DS}$  and  $S_{D1}$ :


$$S_{DS} = 2/3 \cdot S_{MS} \quad S_{D1} = 2/3 \cdot S_{M1}$$



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 158

### IBC2003 – General Procedure

- From  $S_{DS}$  and  $S_{M1}$ , develop the design response spectrum



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 159

### Scaling of Spectra by 2/3 for “Margin of Performance”

- Design with current 2%/50-yr. maps but scale by 2/3.
- Buildings designed according to current procedures assumed to have margin of collapse of 1.5.
- Judgment of “lower bound” margin of collapse given by current design procedures.
- Results in  $2/3 \times 1.5 = 1.0$  deterministic earthquake (where applicable).
- $2/3$  (2500-yr. EQ) = 500-year motions in WUS, but  $2/3$  (2500-yr. EQ)  $\approx$  1600-year motions in EUS
- $2/3$  factor not related to geotechnical performance!



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 160

### Three Classes of Methods for Ground Motion Estimates

- Generalized, simplified (i.e., IBC 2003)
- Site-specific, simplified (i.e., attenuation curves, site amplification factors)  $\Leftarrow$
- Site-specific, rigorous (time history analysis)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 161

### Site-Specific, Simplified

- Relatively simple (chart-based procedures).
- Based on probabilistic motions or deterministic scenarios.
- Can account for regional geological effects (within 2 km of surface; USGS maps assume standard depth for B-C boundary and hard rock).
- Accounts for local site (within few hundred feet of surface) effects in simplified, but more specific manner.
- Better-suited to many geotechnical analyses.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 162

## Site-Specific, Simplified: Comments

- Note IBC 2003 limits site-specific “benefit” (in terms of reduced design motions to 20% for A-E sites.
- Site-specific analysis in some CEUS area less than probabilistic maps values; opposite may be true in WUS.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 163

## Site-Specific Simplified Procedures

Typical deterministic scenario:

1. Knowing fault location and earthquake magnitude, estimate ground motion parameter (i.e, pga or spectral values) for hard rock from attenuation relationships.
2. If appropriate, correct for regional geological conditions such as deep unconsolidated sediments ( $V_s > 700\text{m/s}$  and typically within 2 km of surface)
3. Modify motions for near-surface soils ( $V_s < 700\text{ m/s}$  and within few hundred of surface)\*

\*covered in detail in a following lecture.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 164

## 1. Estimating Motions on Hard Rock

- Typically use region-specific attenuation curve (but can use probabilistic maps also).
- Curves developed from empirical data from recorded motions in most regions.
- Curves in CEUS developed from few small EQs, plus stochastic simulations using methods developed in WUS but with CEUS geological parameters (Q, stress drop, etc.).
- Most curves provide PGA, PGV, and spectral values.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 165

## Ground Motion Attenuation Basic Empirical Relationships

$$\ln \hat{Y} = \ln b_1 + f_1(M) + \ln f_2(R) + \ln f_3(M, R) + \ln f_4(P_i) + \ln \varepsilon$$

$\hat{Y}$  Ground Motion Parameter (e.g. PGA)

$b_1$  Scaling factor

$f_1(M)$  Function of Magnitude

$f_2(R)$  Function of Distance

$f_3(M, R)$  Function of Magnitude and Distance

$f_4(P_i)$  Other Variables

$\varepsilon$  Error Term



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 166

## Ground Motion Attenuation Relationships for Different Conditions

- Central and Eastern US
- Subduction Zone Earthquakes
- Shallow Crustal Earthquakes
- Near-Source Attenuation
- Extensional Tectonic Regions
- Many Others
- Most are for hard rock, some for “soil”

May be developed for any desired quantity  
(PGA, PGV, Spectral Response)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 167





## Ground Motion Attenuation Relationships

Seismological Research Letters  
Volume 68, Number 1  
January/February, 1997



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 168






## 2. Adjustment for Regional Geology


In some regions, the presence of deep unconsolidated sediments ("soil" to geologists, "soft rock" to engineers;  $V_s \approx 700$  m/s) require correction of hard rock values for these conditions. Can use:

- Regional correction curve to adjust hard rock curve; or,
- A "soil" attenuation curve in Step 1 that already includes the effect of the "soil" as soil attenuation curve. In this case, the correction here for Step 2 is not required.

Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 173




### EUS Hard Rock Response Spectrum (adjust with regional soil amplification curve)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 175

### Regional "Soil" Amplification Factors (use to adjust hard rock curve)




- Amplification with respect to hard rock
- Deep soil profile representative of Site Class C soil profile



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 176

### Adjusted Curve for Regional Geology




EPRI (1993)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 177

### "Soil" Attenuation Relationships

- Can use these directly where appropriate and available in lieu of two-step procedure:




Boore and Joyner (1991)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 178

### 3. Adjustment for near-surface soil conditions (within ~30 m depth)


- pga adjustment using amplification factors



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 179

### 3. Adjustment for local soil conditions

- spectral adjustment using amplification factors



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 180


## Three Classes of Methods for Ground Motion Estimates

- Generalized, simplified (i.e., IBC 2003)
- Site-specific, simplified (i.e., attenuation curves, site amplification factors)
- Site-specific, rigorous (time history analysis) ←



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 161

## Typical Earthquake Acceleration Time History Set



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 162

## Time History analyses

- Allows best possible analysis (usually)
- Increasing in usage
- Time histories can be obtained from:
  - Databases of recorded motions such as
    - National and state data catalogs (NSMDS)
    - USGS web page
    - other sources (i.e., NONLIN)
  - By developing the motions using
    - modified recorded motions
    - synthetic motions



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 183

## Obtaining Time Histories

Conditions for which there are few records available:

- Moderate to large earthquakes in CEUS
- Large-magnitude (8+) shallow crustal events
- Near-source, large-magnitude (7.5+) events



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 184

## Time History Analysis

- **Objective:** develop a set or sets of time-histories, usually acceleration time histories, that are representative of site ground motions for the design earthquake(s)\* and that are appropriate for the type of analyses planned.
- Will not be able to predict actual motions, rather interested in *representing characteristics most important for design.*

\* Discussed earlier. The design earthquake can be from deterministic or probabilistic analysis; but, if probabilistic, the uniform hazard spectrum should probably not be used as the target spectrum. Rather, deterministic scenarios should be developed from deaggregation of the PSHA.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 185

## Process for selecting/modifying time histories:



From: (USACE, 2000)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 186

## How many time histories are needed for a typical analysis?

- **For linear analysis, typically 2 or 3**  
(linear system is more influenced by frequency-domain aspects of motion)
- **For non-linear analysis, typically 4 or 5**  
(non-linear systems more influenced by time-domain aspects of record- shape and sequences of pulses, etc.)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 187

## 1. Selecting time histories – key factors:

Most logical procedure is to select available time histories from databases that are reasonably consistent with the design parameters and conditions. Factors to consider include in selection:

- tectonic environment (subduction, shallow crustal, intraplate, etc.)
- earthquake magnitude and fault type
- distance from recording site to fault rupture – want distances within a factor of 2



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 188

## 1. Selecting time histories – key factors:


- site conditions at recording site (want similar)
- response spectra of motions (want similar shape and level to design spectra; also, want to achieve reasonable match by scaling by factor  $\leq 2.0$  (especially if scaling record motions to higher level)
- duration of strong shaking
- if site is near-field (within about 15 km) then acceleration record should contain strong motion pulse similar to that caused directivity, etc.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 189

## 2. Modifying and scaling time histories:

What is the motion at D?



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 190

## 2. Modifying and scaling time histories:


(a) **Simple scaling** – scale motions by single factor to match target spectrum; again limiting the scaling factor to 2.0.

- The required degree-of-fit to target spectrum is project-dependent, but typically want suite of candidate spectra to have average visual fit to target. More important to have conservative fit in period range of interest.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 191


## Simple Scaling to Match Design (Target) Spectrum



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 192

## Degree-of-fit for Suite of Motions:

- Required degree of fit is project dependent and often mandated



From USACE, 2000



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 193

## 2. Modifying and scaling time histories –

(b) **Spectrum matching**– adjustments made in either time domain or frequency domain to change characteristics of the motions:

- Want to maintain time-domain character of recorded motion
- Best to begin with candidate motion that has spectral shape similar to target spectrum
- Best to first scale motion to approximate level of target spectrum before modification



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 194

## Spectrum Matching Methods

(i) **Time-Domain Approach:** (Lilhanand and Tseng, 1988; Abrahamson, 1992).

- Matching accomplished by adding (or subtracting) finite-duration wavelets to (or from) the initial time-history.
- Normally provides a close fit to the target. Best to begin with candidate motion has spectral shape similar to target spectrum.
- Best to first scale motion to approximate level of target spectrum before modification.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 195

## Spectrum Matching Methods


(ii) **Frequency-Domain Approach:** (Gasparini and Vanmarcke 1976; Silva and Lee 1987; Bolt and Gregor 1993).

- Adjusts only the Fourier amplitudes while the Fourier phases are kept unchanged.
- Procedure equivalent to adding or subtracting sinusoids (with the Fourier phases of the initial time-history) in the time domain.
- Does not always provide as close a fit as time-domain approach.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 196

## Spectrum-matched Time Histories




From USACE, 2000



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 197

## Spectra of spectrum-matched time histories:



From USACE, 2000

Figure 5-8. Comparisons of response spectra from the scaled 1971 San Fernando earthquake at Dulick Park (770%) and the frequency-domain matched acceleration.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 198



### Other corrections...

- Ensure records are instrument and base-line corrected, etc.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 199

### 3. Modification for local site conditions

- Dynamic site response analysis is best approach (discussed in following lecture).



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 200

### Real vs. Synthetic Time Histories

- What is considered a “real” record? (i.e., how much modification is allowed?)
- Un-scaled record motion vs. scaled recorded motion vs. synthetic.
- Synthetic motions developed using Fourier phase spectra from real earthquake probably “real” in most important ways.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 201

### Synthetic Time Histories – Pros and Cons

- One main concern: Is true character of real motion present?
- One main advantage: Can develop motions to match regional and site conditions (i.e., motion recorded on outcrops actually have surface wave energy included but we commonly input this to base).
  - there are many data gaps in database of motions (no strong motions for CEUS)
  - certainly better to have reasonable region-specific synthetic motion than inappropriate real motion



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 202

### Developing Synthetic Motions

- Process should be performed by expert, typically seismologist.
- Seismologists typically develop a suite of time histories for hard rock or B-C (soft rock) boundary.
- Geotechnical engineers typically generate top-of-profile motions using site response analysis.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 203

### Synthetic Ground Motion Development

The computational model for generating synthetic seismograms consists of:

- The seismic source process;
- The process of seismic wave propagation from the source region to the design site; and
- Shallow site response (site response is discussed later).



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 204

## Synthetic Ground Motion Development

### Source Parameters Required

- Rupture velocity, rupture initiation point, and slip-time functions over the ruptured area are the primary source parameters needed.

### Propagation (Path) Parameters Required

- Average propagation usually developed with Green's functions -- requires knowledge of the crustal parameters such as the P and S-wave velocities, density, and damping factor (or seismic Q factor, where  $Q = 0.5/\text{damping ratio}$ ).



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 205

## Synthetic Ground Motion Generation

- To model complexity of seismogram, randomness (stochastic model) is often introduced, either in the source process or in the wave propagation.
  - very erratic, irregular high-frequency waves from rupture process usually characterized as a "stochastic" process that must be modeled with randomness
  - deterministic process often used for low-frequency portion of motion
- Hybrid models combine deterministic with random process.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 206

## Synthetic Ground Motion Generation

- With fault slip model and Green's functions, ground motions are computed using the representation theorem (deconvolution process); see Aki and Richards 1980; Hartzell, Frazier, and Brune 1978.
- Simulation procedure simply sums a suite of Green's functions lagged in time (delay caused by the rupture propagation plus the time needed for the seismic waves to travel from the corresponding point source to the site).
  - ⇒ Green's Function is heart of the process.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 207

## Synthetic Ground Motion Methods


(1) Boore (1983): developed Band-Limited-White-Noise model for stochastic simulation of high-frequency ground motions.

- This simulation procedure does not use stochastic slip model.
- Procedure generates random white noise, multiplies it by a window function appropriate for the expected source duration, and then filters the windowed white noise to obtain a time-history having a band-limited Fourier amplitude spectrum specified by the  $\omega^2$ -source Brune (1970) model.
- Incorporates wave propagation effects of a homogeneous crust with  $1/R$  geometrical attenuation.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 208

### Boore (1983) – Illustration of Concept\*:



**Boore (1983)**: Example of time-domain generation of synthetic time history: (a) time history of white noise is filtered in the time domain to produce (b) time history of filtered white noise. Filtered white noise is multiplied by envelope function in (c) to produce the artificial ground motion shown in (d).

\*Figure adapted from Kramer (1996)



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 209

## Synthetic Ground Motion Methods

(2) Silva and Lee (1987): method uses formulation for the Fourier amplitude spectrum similar to Boore, but the phase spectrum from a natural time-history to generate the synthetic time-history.


(3) Publicly available computer codes: Some public domain simulation codes are: RASCAL (Silva and Lee 1987) and SMSIM (Boore 1996).

⇒ The above methods (1 through 3) are well-established.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 210

### Example: Synthetic Motion development with RASCAL



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 211

### Source Modeling for Synthetic Motions

- 1) Point source models (i.e., Brune source spectrum):
  - Simple model where the source is represented by a point.
  - Assumes “stationary” signal; provides average component.
  - Need Magnitude, stress drop  $\Delta\sigma$ , density, crust modulus.
- 2) Finite fault models – modeling the actual rupture:
  - Fault is divided into segments and each segment ruptures after another simulating energy release.
  - Energy radiation from each segment is modeled using Green’s Function.
  - Motion from all segments added up to generate motion at a point from the fault.
  - It models directivity, radiation, and non-stationarity.



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 212

### 1) Point Source Modeling – Brune Model

$$\text{Source } (\omega) = \frac{M_0}{4\pi \cdot \rho \cdot \beta^3} \cdot \frac{\omega^2}{1 + \left(\frac{\omega}{\omega_c}\right)^2}$$

$M_0$  : seismic moment

$\rho$  : mass density of earth’s crust


$\beta$  : shear wave velocity of earth’s crust

$\omega_c$  : corner frequency ( $2\pi f_c$ )  $f_c = 4.91 \times 10^6 \beta \left(\frac{\Delta\sigma}{M_0}\right)^{1/3}$



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 213

### Modeling Source – Brune Model



- Source spectrum for different magnitude earthquakes
- Corner frequency ( $\omega_c$ ) decreases for larger magnitudes (duration  $\propto 1/\omega_c$ )



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 214

### Modeling Path Effects

$$\text{Path } (\omega) = \frac{1}{r} \cdot e^{-\frac{\pi \cdot f \cdot r}{\beta \cdot Q(f)}}$$

$r$  : distance to the source

$f$  : frequency

$\beta$  : shear wave velocity of earth’s crust

$Q$  : quality factor ( $1/2D$ ,  $D$  = damping ratio)


$Q = 200 f^{0.2}$  – Western US

$Q = 680 f^{0.34}$  – Eastern US



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 215


### Modeling Path Effects



- Frequency dependent attenuation
- Smaller attenuation for Eastern US



Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 216



### 2) Finite Fault Model



Total far-field S displacement is constructed by summation of displacement pulses for a large number of sub-faults, randomly distributed on the fault plane.

- Approach taken is similar to that described originally by Zeng et al., *Geophysical Research Letters*, 1994.
- Can model some near-field effects, provides 3 components

**Important Input Parameters:**

- 1) Total Seismic Moment
- 2) Fault dimensions
- 3) Maximum and minimum (circular) sub-fault radii
- 4) Sub-fault stress drop (not necessarily the static stress drop)
- 5) Rupture velocity (spatially constant, etc.)

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 218



$$A_s(f) = Source_s(f) Path_s^{base}(f) Path_s^{sed}(f)$$

$$A_s = Source_s \Phi_s^{base} \exp(-\pi k_s^{base} f) \Phi_s^{sed} \exp(-\pi k_s^{sed} f)$$

$$A_s = C \frac{(2\pi f)^2}{1 + (f/f_c)^2} \Phi_s^{sed} \exp(-\pi k_s^{sed} f)$$

$$Ln \frac{A_s}{(2\pi f)^2} = b - \pi k_s f + \epsilon$$

$$Ln \frac{A_{sp}}{(2\pi f)^2} = b - \pi k_p f + \epsilon$$

$$Ln(A_s / A_{sp}) = b - \pi(k_s - k_p) f + \epsilon$$

$$Ln(V^i) = \sum_{j=1}^n b_j G_j - a \pi f$$

FEMA

### Modeling Considerations – CEUS

- Recurrence rates lower and uncertainties in source mechanisms, locations in CEUS.
- Stronger crustal structure in CEUS, therefore less attenuation.
- Stress drop?
- Too few strong motion recordings.

FEMA Instructional Material Complementing FEMA 451, Design Examples Hazard & Risk Analysis 15-3 - 222