

Traffic Stream Model Relationship

Sabya Mishra

January 22, 2013

Three basic flow characteristics are Flow (q), Speed (u), and Density (k). Let us first define them

Flow (q): defined as the number of vehicles passing a specific point or short section in a given period of time in a single lane (Unit: vehicles/hour/lane)

Speed (u): defined as the ratio of distance traversed per unit distance (Unit: miles/hour)

Density (k): defined as the number of vehicles occupying a section of roadway in a single lane (Unit: vehicles/mile/lane)

There are some unique parameters we need to define; essentially they are the boundary conditions.

q_m : Maximum flow or capacity

u_f : Free flow speed (speed which exists when flow approaches zero)

u_0 : Optimum speed (speed which exists under maximum flow conditions)

k_j : Jam density (density when both flow and speed approaches zero)

k_0 : Optimum density (density when flow is maximum)

Let us consider the following figure which shows three parameters

Consider a linear speed-density relationship. The linear relationship can be interpreted as following

$$u = u_f - \left(\frac{u_f}{k_j} \right) k \quad (1)$$

Speed approaches free flow speed when $k \rightarrow 0$ and $q \rightarrow 0$

Flow approaches maximum flow when $u \rightarrow u_0$ and $k \rightarrow k_0$

Density approaches jam density when $u \rightarrow 0$ and $q \rightarrow 0$

From the units flow-density-speed equation can be written as

$$q = uk \quad (2)$$

Flow density equation can be written as

$$q = u_f k - \left(\frac{u_f}{k_j} \right) k^2 \quad (3)$$

At $q = q_m, k = k_0, (\partial q / \partial k) = 0$,

taking derivative of equation (3), with respect to k

$$0 = u_f - \left(\frac{u_f}{k_j}\right) 2k_0$$

Solving the above produces

$$k_0 = \frac{k_j}{2} \quad (4)$$

Equation (4) suggestd that optimum speed is half of the jam density

Now considering relationship between optimum and free flow speed, equation (3) can be rewritten as the following

$$q_m = u_f k_0 - \left(\frac{u_f}{k_j}\right) k_0^2 \quad (5)$$

In equation (5) replace, $q_m = u_0 k_0$

$$u_0 k_0 = u_f k_0 - \left(\frac{u_f}{k_j}\right) k_0^2 \quad (6)$$

Solving equation (6) we get

$$u_0 = u_f - \left(\frac{u_f}{k_j}\right) k_0 \quad (7)$$

We know from equationIn equation replace $k_0 = \frac{k_j}{2}$ in equation (7), and solving we will get

$$u_0 = \frac{u_f}{2} \quad (8)$$

By combining equation (7), and (8),

$$q_0 = k_0 u_0 = \frac{u_f k_j}{4} \quad (9)$$

All the above forumation of traffic stream models are derived using the assumption that the relationship between speed and density is linear. These equations may not hold true if this assumption is violated.